

Beklentilerinizden daha fazlası...
More Than Your Expectations...

INS
MAKINA



CONCRETE BATCHING PLANTS
BETON SANTRALLERİ

BETON SANTRALLERİ



CONCRETE BATCHING PLANTS



SANTRALLERİ



> MOBİL ÜNİTEDE TİTREŞİMLİ ELEKLER

Titreşimli elekler tüm dere ve ocak tesislerinde kırılmış malzemeyi istenilen ebatlarda ayırmak için kullanılırlar. Elek ön olukların tüm katları cıvatalı biçimde ayrılabilir. Elek kasaları komple cıvatalıdır. Tüm elek makinaları yataklamaları hassas borverk tezgahlarında işlenmektedir. Ana mil malzemesi 4140 yüksek kalite çelik ile son sistem tezgahlarımızda imal edilir. Elek yataklamasında çift sıra rulman sistemide kullanılmaktadır.

> MOBILE UNIT VIBRATING SCREENS

Vibrating screens are used to separate the desired material was broken in all streams and quarries plant size. Screens can be divided in such a way bolted all layers of the front groove. Sieve boxes are bolted to complete. All screens are processed in machines boring mills beddings precision machine tools. Main shaft material is manufactured in our latest system stalls with 4140 high quality steel. Screens are used in a double row bearing to the bearing system.

MODEL / MODEL		ANMA ÖLÇÜSÜ DIMENSIONS (mm x mm)	ELEME ALANI SCREEN AREA (m ²)	SCREEN SLOPE PENTE DE CRIBLAGE (derece angle)	MOTOR MOTOR (kw/rpm)
İNS-TE-1020-2/OT		1000 x 2000	2 m ²	18°	5.5 - 1500
İNS-TE-1230-2/OT		1200 x 3000	3.6 m ²	18°	7.5 - 1500
İNS-TE-1240-2/OT		1200 x 4000	4.8 m ²	18°	11 - 1500
İNS-TE-1650-2/OT	2 KATLI	1600 x 5000	8 m ²	18°	15 - 1500
İNS-TE-1850-2/OT	2 DECKS	1800 x 5000	9 m ²	18°	15 - 1500
İNS-TE-2050-2/OT		2000 x 5000	10 m ²	18°	18.5 - 1500
İNS-TE-2060-2/OT		2000 x 6000	12 m ²	18°	22 - 1500
İNS-TE-2260-2/OT		2200 x 6000	13.2 m ²	18°	22 - 1500
İNS-TE-1240-3/OT		1200 x 4000	4.8 m ²	18°	11 - 1500
İNS-TE-1650-3/OT		1600 x 5000	8 m ²	18°	15 - 1500
İNS-TE-1850-3/OT	3 KATLI	1800 x 5000	9 m ²	18°	18.5 - 1500
İNS-TE-2050-3/OT	3 DECKS	2000 x 5000	10 m ²	18°	18.5 - 1500
İNS-TE-2060-3/OT		2000 x 6000	12 m ²	18°	22 - 1500
İNS-TE-2260-3/OT		2200 x 6000	13.2 m ²	18°	30 - 1500
İNS-TE-1240-4/OT		1200 x 4000	4.8 m ²	18°	11 - 1500
İNS-TE-1650-4/OT		1600 x 5000	8 m ²	18°	15 - 1500
İNS-TE-1850-4/OT	4 KATLI	1800 x 5000	9 m ²	18°	18.5 - 1500
İNS-TE-2050-4/OT	4 DECKS	2000 x 5000	10 m ²	18°	22 - 1500
İNS-TE-2060-4/OT		2000 x 6000	12 m ²	18°	30 - 1500
İNS-TE-2260-4/OT		2200 x 6000	13.2 m ²	18°	30 - 1500

> MOBİL ÜNİTEDE HELEZON YIKAYICILAR

Özellikle dere yataklarından eleme yıkama ünitesi ile elde edilen 0-5 mm doğal kumun içerisinde bulunan kil-çamur v.b. gibi kirliliğin yıkanarak temizlenmesi amacıyla kullanılır. Helisler üzerindeki lastik kaplamaları ile uzun ömürlü çalışma performansı sunar.

> SPIRAL WASHERS MOBILE UNIT

Especially obtained by screening and washing unit found in the natural sand from the river bed of 0-5 mm. clay - mud etc. As it used in order to wash out the impurities. with a rubber coating on helices longevity study presents performance.

MODEL / MODEL	ANMA ÖLÇÜSÜ DIMENSIONS (mm x mm)	HELEZON ADET SCREW QTY (adet pcs)	KAPASİTE CAPACITY (ton/saat/tons/hour)	SU İHTİYACI WATER NEED (ton/saat/tons/hour)	MOTOR MOTOR (kw / rpm)
İNS-YH-500/5000/1	Ø500 x 5000	1	20 - 30	20 - 50	5.5 - 66
İNS-YH-600/6000/1	Ø600 x 6000	1	25 - 40	25 - 60	7.5 - 66
İNS-YH-600/6000/2	Ø600 x 6000	2	50 - 80	50 - 120	2 x 7.5 - 66
İNS-YH-750/7500/2	Ø750 x 7500	2	80 - 100	60 - 150	2 x 11 - 66



www.instmakina.com


MOBİL ELEME VE YIKAMA TESİSLERİ
MOBILE SCREENING AND WASHING PLANTS



Beklentilerinizden daha fazlası...
More Than Your Expectations...



BETON SANTRALLERİ



CONCRETE BATCHING PLANTS



CONCRETE BATCHING PLANTS
BETON SANTRALLERİ

İNS MAKİNA BETON SANTRALLERİ
İMALAT MADENCİLİK İNŞ. TAAH. SAN. TİC. LTD. ŞTİ.

Saray Mah. 126. Cadde No:13
Kahramankazan / Ankara / Turkey
Tel : +90 312 386 08 44
+90 312 386 08 46
Fax : +90 312 386 08 49

info@insmakina.com
www.insmakina.com

www.concretebatchingplants.com.tr